

UT-16000(06)

RETRACTABLE FALL ARREST BLOCKS, WIRE ROPE FALL ARREST BLOCK



UT-16000(06)

RETRACTABLE FALL ARREST BLOCK

Features

- Casing made up of high impact strength Polymer, to prevent damage and is nearly indestructible.
- Comes in Galvanized Steel Wire Rope of dia 4.5 mm.
- Has UT-H11 Hook with Load Indicator at attachment end.
- Anchorage Eye with swivel action. Prevents undue twist of rope while working or in the event of a Fall.
- Minimum Breaking Strength is 15kN.

Certification

Conforms to : EN 360:2002



WEIGHT



Tested at 140 kgs



TECHNICAL SNAPSHOT

Part code	Material of casing	Material and Dia of lifeline	Breaking Strength	Attachment End	Anchorage End	Certification	Weight(kgs)
UT-16000(06)	High impact Strength polymer	Galvanized Steel Wire Rope of dia 4.5 mm.	15kN	Has UT-H11 Hook with Load Indicator at attachment end	Anchorage Eye with swivel action	EN 360:2002	3.5kg



For more Query Contact Us

Contact Us

About us

Safety is Our Mission



ufsprotects.co.uk

We at UFS Protects UK Ltd. would like to introduce ourselves as a trusted company in the industry.



Search

INFORMATION

[Home](#)

[About Us](#)

[Certificate](#)

[Contact](#)

COMPANY

[Meet Our Team](#)

[Career](#)

[Catalogue](#)



Unit 5 Rossington Business Park West Carr Road, Retford, Nottinghamshire, United kingdom
7th floor, Office (707) City Avenue Building Next to Deira City Centre, Port Saeed, Deira, Dubai



+971-503016744



varun@ufsprotects.com

salesint@ufsprotects.com